



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

2/PT3

10/530175
JC06 Rec'd T/PTO 04 APR 2005

1

"Equipment for cold-drawing a metal wire."

DESCRIPTION

* * * *

5 The present invention refers to an equipment for cold-drawing a metal wire.

Drawing, that is the reduction of the section of a wire or other metal article through threading dies, is obtained by pulling the material through the threading die by means of drawbench machines.

10 A commonly used technique specially for metal wires with round section enables the drawing of metal wire to be obtained by means of successive section reductions due to the wire passing through threading dies positioned one after the other and contained, together with a tank containing lubricant for the wire, in a single equipment for wiredrawing. Lubrication in this equipment is achieved by means of interposition of lubricant between
15 the metal wire and the threading die because of both the motion of the wire towards the threading die and the spatial geometric profile of the threading die itself.

Apparatus that enables optimal lubrication to be achieved during the entire cold-drawing operation has been described in the Italian Patent No.
20 1230396. This apparatus comprises an external body internally fitted with a tank containing a lubrication material. Said tank has at one end an input hole for a metal wire to be drawn, and is fitted at the other end with a first sleeve fitted with a cylindrical hole whose diameter exceeds that of the wire and a threading die fitted with a truncated cone hole with decreasing diameter
25 towards the output so as to enable the reduction of the diameter of the wire. A spacing element of suitable conformation is positioned between the threading die and the sleeve for joining the output holes from the sleeve and the input holes into the threading die and which acts as gasket for the equipment's cooling water.

30 Another apparatus for cold drawing of a metal wire is described in the

Italian Patent application No. MI99U000587 dated 24th September 1999.

The apparatus is similar to the previously described apparatus except for the fact that it does not comprise the spacing element between the sleeve with cylindrical hole and the threading die with conical hole. The sleeve
5 terminates with an extension inserted into the conical hole of the threading die so that it is impermeable to the apparatus cooling water. Both the sleeve and the threading die are held in position by means of a threaded plug fixed to a support which in turn is fixed by means of screws onto the external body of the apparatus.

10 Nevertheless, mounting the threading die onto the sleeve can become a complicated operation; in fact this operation sometimes has to be repeated various times because it is difficult to insert the threading die onto the sleeve with simultaneous fastening of the threaded plug onto the body.

15 In view of the state of the technique described, the object of the present invention is to produce an equipment for cold-drawing a metal wire that presents greater advantages in terms of mounting and thus overall cost of the equipment.

20 In accordance with the present invention, said object is achieved by an equipment for cold-drawing a metal wire, said equipment comprising a succession of a sleeve with a cylindrical hole and a threading die with a conical hole in the advance path of the wire, said sleeve being inserted into a support and terminating with an extension inserted into said conical hole of said threading die, characterised in that said support has a first annular projection and said threading die has a second annular projection coupled to
25 said first projection so as to keep said sleeve and said threading die in position.

30 The characteristics and the advantages of the present invention will appear evident from the following detailed description of an embodiment thereof, illustrated as non-limiting example in the enclosed drawings, in which:

Figure 1 shows a transversal section of the equipment according to the invention;

Figure 2 shows a part of the equipment of Figure 1 more in detail.

With reference to Figure 1, the equipment comprises an external body 1 fitted internally with a tank 2 containing calcium or sodium-based stearates or other lubrication material. Said tank 2 presents at one side end an input hole 3 for the passage of a metal wire 4 (steel, copper, aluminium, etc.) that has to be drawn. The diameter of the hole 3 is greater than the section of the metal wire 4. The tank 2 is also fitted at the other side end with a sleeve 5 contained in a casing 6, generally made of steel, and comprising a circular-sectioned body 7, generally made of tungsten carbide commonly called hard metal or widia, fitted with a hole which in its central part 8 has a cylindrical conformation with a diameter just greater than that of the wire 4 in input.

As can be seen better in Figure 2, said circular-sectioned body 7 has in one of its ends a truncated cone extension 9 that juts out of the casing 6 in the central part of the casing. Said casing 6 has in addition a lower annular projection 20 on the external cylindrical skirt 21.

The extension 9 is inserted in a special funnel-shaped cavity 10 entering a threading die 11. The threading die 11 comprises a casing 12, generally made of steel, comprising a circular-sectioned body 13, generally made of widia, fitted with a conical hole which in its central part 14 has a truncated-cone conformation with decreasing diameter and whose longitudinal axis of symmetry coincides with the axis of symmetry of the hole of the sleeve 5. The casing 12 presents an upper annular projection 22.

The threading die 11 is held in position, thus similarly providing as for the position of the sleeve 5, by coupling the annular projection 22 of the threading die 11 with the annular projection 20 of the casing 6. This is carried out by means of manual pressure mounting of the threading die 11 on the casing 6.

An annular gasket 23 is also provided on the part 24 of the annular

projection 20 that comes up against the annular projection 22 of the threading die 11.

5 The block consisting of the threading die 11 and the sleeve 5 coupled together is held in position on the body 1 by a threaded plug 15 fixed to the external body 1 and which has a discharging hole 17 passing through for the output of the wire 4.

10 In the drawing operation in the structure described, the metal wire 4 passing through the tank 2 picks up the lubricant contained therein. Then the wire 4 passes through the sleeve 5 without any reduction of diameter and through the threading die 11 with truncated cone hole where the wiredrawing is carried out. The lubricant reaches the wire 4 together with the sleeve 5 where it has pressure and keeps the lubricating properties suitable for the correct lubrication of the wire 4 subjected to drawing.

15 Mounting of the threading die 11 on the sleeve 5 by means of insertion of the truncated cone extension 9 in the funnel-shaped cavity 10 must be made so as to guarantee the impermeable characteristic of the structure in relation to the cooling water of the equipment.

20 Mounting the equipment results simple to carry out and enables reduction of the overall cost of said operation. In fact, times for mounting the threading die 11 on the casing 6 containing the sleeve 5 are reduced as the presence of the plug 15 is now required only for positioning the sleeve-threading die block on the body 1 given that both the sleeve 5 and the threading die 11 are already positioned in relation to each other by coupling the projections 20 and 22

CLAIMS

1. Equipment for cold-drawing a metal wire, said equipment comprising a succession of a sleeve (5) with a cylindrical hole (8) and a threading die (11) with a conical hole (14) in the advance path of the wire, said sleeve (5) being inserted into a support (6) and terminating with an extension (9) inserted into said conical hole (14) of said threading die (11), characterised in that said support (6) has a first annular projection (20) and said threading die (11) has a second annular projection (22) coupled to said first projection (20) so as to keep said sleeve (5) and said threading die (11) in position.
2. Equipment according to claim 1, characterised in that it comprises an annular gasket (23) in the part (24) of said first projection (20) that comes up against said second projection (22).
3. Equipment according to claim 1, characterised in that said extension (9) of the sleeve (5) is inserted into the conical hole (14) of the threading die (11) so that it is impermeable to the cooling water of said equipment.
4. Equipment according to claim 1, characterised in that it comprises a wire lubrication tank (2) and in that the sleeve (5) and the threading die (11) are positioned at the output of said tank (2).

“Equipment for cold-drawing a metal wire.”

* * * * *

ABSTRACT

5 The following invention refers to an equipment for cold-drawing a
metal wire. The equipment comprises a succession of a sleeve (5) with a
cylindrical hole (8) and a threading die (11) with a conical hole (14). The
sleeve (5) is inserted into a support (6) and terminates with an extension (9)
inserted into said conical hole (14) of the threading die (11). The support (6)
has a first annular projection (20) and the threading die (11) has a second
10 annular projection (22) coupled to said first projection (20) so as to keep the
sleeve (5) and the threading die (11) in position. (Fig. 1).





FIG.1

FIG.2

INTERNATIONAL SEARCH REPORT

Intern: Application No
PCT/EP 03/11172

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B21C3/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B21C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

PAJ, WPI Data, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 07, 31 July 1997 (1997-07-31) -& JP 09 057333 A (SHOWA ELECTRIC WIRE & CABLE CO LTD), 4 March 1997 (1997-03-04) abstract; figure 1	1, 4
A	IT 1 230 396 B (VASSENA GIUSEPPE) 21 October 1991 (1991-10-21) cited in the application figure 1	1, 4
A	EP 0 013 012 A (AKAD WISSENSCHAFTEN DDR) 9 July 1980 (1980-07-09) figure 2	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the International filing date but later than the priority date claimed

- *T* later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the International search

29 January 2004

Date of mailing of the International search report

16/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ritter, F

Information on patent family members

Inter

Application No

PCT/EP 03/11172

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 09057333	A	04-03-1997	NONE	
IT 1230396	B	21-10-1991	NONE	
EP 0013012	A	09-07-1980	DD 147209 A1	25-03-1981
			DD 147205 A1	25-03-1981
			DD 146793 A1	04-03-1981
			DE 2967068 D1	26-07-1984
			EP 0013012 A1	09-07-1980